

# PREMIUM DRY SMALL DIAMETER SEGMENTED BLADES

**PREMIUM BLADES** - Designed with a high diamond concentration and a .250 diamond bearing area. Excellent for longer blade life, critical cutting, lowest overall cutting cost and large jobs.

**FLUSH CUT COLLAR SYSTEM** - Wel-Co produces a solid brass collar system which allows cuts to be made flush to the wall or ceiling surface. The system is designed for use on electric right angle grinders and it is reusable. It can be used on the Wel-Co's segmented and serrated blades.

Size	MSRP
4" x .090" x 7/8"	\$ 64
<b>4" x .230" x 7/8"</b>	<b>\$ 102</b>
4.5" x .090" x 7/8"	\$ 73
<b>4.5" x .230" x 7/8"</b>	<b>\$ 113</b>
5" x .090" x 7/8"	\$ 82
<b>5" x .230" x 7/8"</b>	<b>\$ 124</b>
6" x .090" x 7/8"	\$ 96
<b>6" x .230" x 7/8"</b>	<b>\$ 147</b>
7" x .090" x UA	\$ 113
<b>7" x .230" x UA</b>	<b>\$ 173</b>
8" x .090" x UA	\$ 136
8" x .125" x UA	\$ 164
<b>8" x .230" x UA</b>	<b>\$ 213</b>
9" x .090" x 5/8"	\$ 153
10" x .090" x 5/8"	\$ 171

**Sizes in blue are commonly used for tuck pointing and crack chasing.**



## Application Specs

PDC -1P	For cutting harder ranges of masonry materials such as cured concrete with hard aggregate, brick, stone, and brick pavers. Ideal for tuck-pointing hard mortar joints with hard quartz aggregate and dull sand
PDC -2P	General purpose for cutting medium hard masonry materials such as cured concrete, brick, stone, concrete pavers and concrete roofing tiles. Ideal for tuck-pointing mortar joints with medium hard aggregate and medium sand
PDC -3P	For cutting softer materials such as asphalt, green concrete, or concrete block. Ideal for tuck-pointing mortar joints with soft aggregate and sharp sand
PDC-2PV	Designed to open cracks in cured concrete on a right angle grinder (4" only) Available size: 4" x .250 x 7/8". MSRP \$ 152.00